BLUETOOTH® RING SCANNER

EASY TO PAIR. EASY TO SCAN. EASY TO SEE THE DIFFERENCE.

The 8650 Bluetooth® Ring Scanner is a comfortable and easy-to-implement productivity tool for all mobile operators who regularly need to scan barcodes. The small, lightweight device rests on the finger, with the Bluetooth module worn comfortably on the wrist. Using our unique EZ-Pair process, pairing with any Bluetooth-enabled handheld, wearable, fixed-station or vehicle-mount computer is as simple as a single scan. Once in use, the Bluetooth Ring Scanner reliably transmits critical data from up to 30 feet away.* Operators gain unsurpassed freedom of movement to perform barcode reading tasks quickly, safely and comfortably - all while keeping both hands free.

In a business climate where every advantage matters, the Bluetooth Ring Scanner can deliver a 10-15% gain in productivity over a tethered scanner or other solution. What will your business do with an extra 10%?

To learn more about the 8650 Bluetooth Ring Scanner or schedule a demo, please visit lxe.com/btrs.

VERSATILE
1D or 2D imager available

RUGGED
Tough magnesium housing protects from bumps and drops

BUILT WITH THE USER IN MIND
Hygienic velcro strips are washable and replaceable

1-click reversal from right-handed to left-handed

IP 54

4ft

LXE | FLEX | Wearable Computers

8650 BTRS

TECHNICAL SPECIFICATIONS

BLUETOOTH® MODULE

- Bluetooth Version 2.0
- Supports LXE EZ Pairing, operates in either master or slave mode
- SPP Bluetooth profile
- 128-bit encryption
- Class 2 radio, 30 foot (10m) roaming range
- Power-management control
- Configuration via scanned barcodes

ENCLOSURE

- Bluetooth module and ring body are ABS plastic
- Ring face & top are magnesium alloy
- Weight: Bluetooth module, battery, ring & hand strap: 4.8oz (136g)

BATTERY

- 3.7V, 750mAh Li-Ion battery
- Recharging time 4 hrs

ENVIRONMENTAL

- Operating temperature: -4° to +122°F (-20° to +50°C)
- Storage temperature: -22° to + 122°F (-30° to +50°C)
- Humidity: 5% to 95% RH non-condensing
- Ingress Protection: IEC 60529 compliant to IP54
- Drop specification 4ft (1.22m) multiple drops to concrete

OPTIONAL SCAN WEDGE SOFTWARE

For Windows® XP Connections

- Manage Bluetooth connections & security for up to 7 scanners
- Direct scanned data to other applications
- Manipulate scanned data w/ automatic prefix, suffix functions

DATA CAPTURE

1D Laser

- Range 2.2" (56mm) to 45" (1143mm) typical range

1D Barcode Symbologies

- Chinese 2 of 5
- Codabar
- Code 11
- Code 128
- Code 39
- Code 93
- Discrete 2 of 5
- Interleaved 2 of 5
- MSI Plessey
- RSS
- UPC/EAN

1D/2D Imager

- 2.3" (58mm) to 22" (559mm) typical range

2D Barcode Symbologies

- PDF417,
- MicroPDF
- Code 128 Emul
- Data Matrix
- Maxicode
- QR code
- Postal codes

CUSTOMIZATIONS

Accessories

- 8-bay or single-bay charger
- Large or small wrist strap
- Replacement finger-strap kits

ORACLE PARTNER

SOFTWARE SAP PARTNER

CISCO Technology

Copyright © 2010 LXE Inc. All rights reserved. Specifications are subject to change without notice. All names, products, and services mentioned are the trademarks or registered marks of their respective organizations.

125 Technology Parkway
Norcross, GA 30092
1-800-664-4593
www.lxe.com